A comparison between measurements of the F-layer critical frequency and values der ved from the PRISM adjustment algorithm applied to total electron contendata in the equatorial region

A. J. Mannucci¹, D. N. Anderson² and A. M. Abdu³

- 1. Jet Propulsion Laboratory, MS 238-700, 4800 Oak Grove Drive, Pasadena, CA 91109
- 2. Ionospheric Effects Division, Phillips Laboratory, Hanscom AFB, Lexington MA 01731
- 3. Instituto Nacional de Pesquisas Espacias, Av. Dos Astronautas, 1758 Caixa Postal 515, 12.227-010-Sao Jose Dos Campos-SP-Brazil

The Parametrized Real-Time Ionosphere Specification Model (PRISM) is a global ionospheric specification model that can incorporate real-time data to compute accurate electron density profiles. Two important data types which can be ingested into PRISM are ionosonde data (critical frequencies and heights) and total electron content (TEC). The adjustment algorithm incorporates measurements of F-layer critical frequencies (f_0F2) directly, but the TEC data must first be converted to equivalent f_0F2 values. To assess the accuracy of the conversion algorithm in the equatorial region, TEC data from a global positioning system (GPS) receiver in Fortaleza, Brazil (3.9S, 38.4W) is used to compute f_0F2 values above a nearby ionosonde station (Sao Luis, 2.6S, 44.3W) for comparison with measured values. Time series of computed and measured f_0F2 will be presented for the period October 25-November 9, 1993, using ionosonde and GPS data recorded at 15 minute and 30 second intervals respectively. This comparison can be used to suggest methods of optimizing the PRISM adjustment algorithm for TEC data obtained at low latitudes.